

IN THE CLAIMS:

Please **CANCEL** claims 2-3, 24-60, 78, 104, and 112 without prejudice or disclaimer.

Please **AMEND** claims 1, 4, 9, 12-13, 16-17, 23, 77, 97-99, 103, 105-111, and 113 as follows.

Please **ADD** claims 114-116 as follows.

1. (Currently Amended) An apparatus in a cellular communications network, comprising:

a monitor configured to monitor at least one parameter related to a connection between a mobile station and a support node, said at least one parameter comprising user activity; and

a determining unit configured to determine ~~if whether~~ the connection between said support node and said mobile station is to be released ~~dependent based~~ solely on said at least one parameter monitored by said monitor,

wherein the apparatus is configured to provide the connection between the mobile station and the support node, and further configured to completely release the connection when there is user inactivity for a predetermined period of time.

2-3. (Cancelled)

4. (Currently Amended) The apparatus as claimed in claim 12, wherein said apparatus is further configured to send a message to the support node indicating that said connection has been released.

5. (Previously Presented) The apparatus as claimed in claim 1, wherein said apparatus is further configured to send a request for the connection to be released to said mobile station.

6. (Previously Presented) The apparatus as claimed in claim 5, wherein the support node is configured to send a connection release command to said apparatus in response to the release request received by said apparatus, and wherein said apparatus is further configured to control the release of said connection.

7. (Previously Presented) The apparatus as claimed in claim 6, wherein said apparatus is further configured to send a release request to said mobile station in response to the release command received from said support node.

8. (Previously Presented) The apparatus as claimed in claim 7, wherein said apparatus is further configured to send a message to said support node advising that the connection has been released.

9. (Currently Amended) An apparatus in a cellular communications network, comprising:

a monitor configured to monitor at least one parameter related to a connection between a mobile station and a support node, said at least one parameter comprising an elapsed time since a last use of the connection; and

a determining unit configured to determine ~~if whether~~ the connection between said support node and said mobile station is to be released ~~dependent based~~ solely on said at least one parameter monitored by said monitor, ~~wherein said at least one parameter comprises an elapsed time since the last use of the connection, wherein said determining unit is further configured to determine that the connection is to be released if said monitor indicates that the connection has not been used for a predetermined time, and~~

wherein the apparatus is configured to provide the connection between the mobile station and the support node, and further configured to completely release the connection when the connection has not been used for a predetermined time.

10. (Previously Presented) The apparatus as claimed in claim 9, wherein the predetermined time depends on the type of traffic for which the connection is intended.

11. (Previously Presented) The apparatus as claimed in claim 9, wherein the predetermined time depends on the quality of service profile of the traffic for which the connection is intended.

12. (Currently Amended) An apparatus in a cellular communications network, comprising:

a monitor configured to monitor at least one parameter related to a connection between a mobile station and a support node, said at least one parameter comprising a state of said mobile station; and

a determining unit configured to determine ~~if whether~~ the connection between said support node and said mobile station is to be released ~~dependent-based~~ solely on said at least one parameter monitored by said ~~monitoring means,~~ monitor,

~~wherein said at least one parameter comprises a state of said mobile station,~~

~~wherein said determining unit is further configured to determine if the connection is to be released based on the state of the mobile station determined by said monitor, and~~

wherein the apparatus is configured to provide the connection between the mobile station and the support node, and further configured to completely release the connection based on the state of the mobile station.

13. (Currently Amended) An apparatus in a cellular communications network, comprising:

a monitor configured to monitor at least one parameter related to a connection between a mobile station and a support node, said at least one parameter comprising a movement of the mobile station; and

a determining unit configured to determine ~~if whether~~ the connection between said support node and said mobile station is to be released ~~dependent-based~~ solely on said at least one parameter monitored by said monitor,

~~wherein said at least one parameter comprises a movement of the mobile station, and said determining unit is further configured to determine if the connection should be released based on the movement of the mobile station monitored by said monitor, and~~

wherein the apparatus is configured to provide the connection between the mobile station and the support node, and further configured to completely release the connection based on the movement of the mobile station.

14. (Previously Presented) The apparatus as claimed in claim 13, wherein an amount of updating information received in a given time from the mobile station is used as a measure of the movement of the mobile station.

15. (Previously Presented) The apparatus as claimed in claim 14, wherein said updating information comprises universal mobile telecommunication systems terrestrial radio access network registration area updates.

16. (Currently Amended) An apparatus in a cellular communications network, comprising:

a monitor configured to monitor at least one parameter related to a connection between a mobile station and a support node, said at least one parameter comprising a location of the mobile station; and

a determining unit configured to determine if whether the connection between said support node and said mobile station is to be released ~~dependent-based~~ solely on said at least one parameter monitored by said monitor, ~~wherein said at least one parameter comprises a location of the mobile station, and said determining unit is further configured to determine if the connection should be released based on the location of said mobile station monitored by said monitor, and~~

wherein the apparatus is configured to provide the connection between the mobile station and the support node, and further configured to completely release the connection based on the location of the mobile station.

17. (Currently Amended) The apparatus as claimed in claim 16, wherein said at least one parameter comprises associations of the mobile station with different apparatus, and said determining unit being further configured to determine that the connection should be released if when said monitor indicates that the mobile station is associated with a different apparatus.

18. (Cancelled)

19. (Previously Presented) A cellular communications network, comprising:
an apparatus as claimed in claim 1, a mobile station and a support node.

20. (Cancelled)

21. (Previously Presented) The cellular communications network as claimed in claim 19, wherein said support node is a serving general packet radio service support node.

22. (Previously Presented) The cellular communications network as claimed in claim 19, wherein said network operates in accordance with a universal mobile telecommunication systems standard.

23. (Currently Amended) The apparatus as claimed in claim 13, wherein said apparatus is further configured to send a message to the support node indicating that said connection has been released.

24-76. (Cancelled)

77. (Currently Amended) A cellular communications network, comprising:
an apparatus as claimed in claim 12, a mobile station and a support node.

78. (Cancelled)

79. (Previously Presented) A cellular communications network, comprising:
an apparatus as claimed in claim 4, a mobile station and a support node.

80. (Previously Presented) A cellular communications network, comprising:
an apparatus as claimed in claim 5, a mobile station and a support node.

81. (Previously Presented) A cellular communications network, comprising:
an apparatus as claimed in claim 6, a mobile station and a support node.

82. (Previously Presented) A cellular communications network, comprising:
an apparatus as claimed in claim 7, a mobile station and a support node.

83. (Previously Presented) A cellular communications network, comprising:
an apparatus as claimed in claim 8, a mobile station and a support node.

84. (Previously Presented) A cellular communications network, comprising:
an apparatus as claimed in claim 9, a mobile station and a support node.

85. (Previously Presented) A cellular communications network, comprising:
an apparatus as claimed in claim 10, a mobile station and a support node.
86. (Previously Presented) A cellular communications network, comprising:
an apparatus as claimed in claim 11, a mobile station and a support node.
87. (Previously Presented) A cellular communications network, comprising:
an apparatus as claimed in claim 12, a mobile station and a support node.
88. (Previously Presented) A cellular communications network, comprising:
an apparatus as claimed in claim 13, a mobile station and a support node.
89. (Previously Presented) A cellular communications network, comprising:
an apparatus as claimed in claim 14, a mobile station and a support node.
90. (Previously Presented) A cellular communications network, comprising:
an apparatus as claimed in claim 15, a mobile station and a support node.
91. (Previously Presented) A cellular communications network, comprising:
an apparatus as claimed in claim 16, a mobile station and a support node.

92. (Previously Presented) A cellular communications network, comprising:
an apparatus as claimed in claim 17, a mobile station and a support node.

93-95. (Cancelled)

96. (Previously Presented) The cellular communications network as claimed in claim 21, wherein said cellular communications network operates in accordance with a universal mobile telecommunication systems standard.

97. (Currently Amended) An apparatus, comprising:
a monitor configured to monitor at least one parameter related to a connection between a mobile station and a support node, said at least one parameter comprising at least one of a state of the mobile station, a movement of the mobile station, or an amount of communications between the mobile station and a radio network controller; and
a determining unit configured to determine whether the connection between said support node and said mobile station is to be released based solely on said at least one parameter monitored by said monitor,
wherein the apparatus is configured to provide the connection between the mobile station and the support node, and further configured to completely release the connection based on said at least one parameter.

~~The apparatus of claim 1, wherein said at least one parameter comprises at least one of a state of the mobile station, movement of the mobile station, or an amount of communications between the mobile station and a radio network controller.~~

98. (Currently Amended) An apparatus, comprising:

a processor configured to monitor at least one parameter of a connection established between a mobile station and a support node and to determine ~~if whether~~ the connection between said support node and said mobile station is to be released ~~dependent~~ based solely on said at least one parameter,

wherein the apparatus is implemented in a cellular communication network, and

wherein said apparatus is configured to provide the connection between the mobile station and the support node, and further configured to completely release the connection based on said at least one parameter.

99. (Currently Amended) A method, comprising:

establishing a connection between a mobile station and a support node in a cellular communications network through a radio network controller;

monitoring, at the radio network controller, at least one parameter related to the connection between the mobile station and the support node; ~~and~~

determining, at the radio network controller, ~~if whether~~ the connection between said support node and said mobile station is to be released ~~dependent~~ based solely on said at least one parameter; and

releasing completely, by the radio network controller, the connection between said support node and said mobile station based on said at least one parameter.

100. (Previously Presented) The apparatus of claim 98, wherein said support node is a serving general packet radio service support node.

101. (Cancelled)

102. (Previously Presented) The apparatus as claimed in claim 1, wherein said apparatus is further configured to release the connection between the apparatus and said mobile station dependent solely on only one parameter monitored by said monitor.

103. (Currently Amended) The method as claimed in claim 99, wherein said at least one parameter comprises user activity, and determining ~~releasing~~ to release said connection ~~if when~~ there is user inactivity for a predetermined period of time.

104. (Cancelled)

105. (Currently Amended) The method as claimed in claim 99, wherein the monitoring comprises monitoring only one parameter related to the connection between the mobile station and the support node, ~~is monitored and~~ wherein the determining comprises determining to release ~~releasing~~ the connection between a network element and said mobile station ~~dependent-based~~ solely on the only one monitored parameter, ~~monitored.~~

106. (Currently Amended) An apparatus in a cellular communications network, comprising:

monitoring means for monitoring at least one parameter related to a connection between a mobile station and a support node, said at least one parameter comprising an elapsed time since a last use of the connection; and

determining means for determining ~~if whether~~ the connection between said support node and said mobile station is to be released ~~dependent-based~~ solely on said at least one parameter monitored by said ~~means for monitoring means, wherein said at least one parameter comprises an elapsed time since the last use of the connection, and said determining means determines that the connection is to be released if said monitoring means indicates that the connection has not been used for a predetermined time,~~

wherein the apparatus is configured to provide the connection between the mobile station and the support node, and further configured to completely release the connection when the connection has not been used for a predetermined time.

107. (Currently Amended) An apparatus in a cellular communications network, comprising:

monitoring means for monitoring at least one parameter related to a connection between a mobile station and an support node, said at least one parameter comprising a state of said mobile station; and

determining means for determining ~~if-whether~~ the connection between said support node sand said mobile station is to be released ~~dependent-based~~ solely on said at least one parameter monitored by said monitoring means, ~~wherein said at least one parameter comprises a state of said mobile station, and said determining means is configured to determine if the connection is to be released based on the state of the mobile station determined by said monitoring means,~~

wherein the apparatus is configured to provide the connection between the mobile station and the support node, and further configured to completely release the connection based on the state of the mobile station.

108. (Currently Amended) An apparatus in a cellular communications network, comprising:

monitoring means for monitoring at least one parameter related to a connection between a mobile station and an support node, said at least one parameter comprising a movement of the mobile station; and

determining means for determining ~~if-whether~~ the connection between said support node and said mobile station is to be released ~~dependent-based~~ solely on said at least one parameter monitored by said monitoring means, ~~wherein said at least one parameter comprises a movement of the mobile station, and said determining means is configured to determine if the connection should be released based on the movement of the mobile station monitored by said monitoring means,~~

wherein the apparatus is configured to provide the connection between the mobile station and the support node, and further configured to completely release the connection based on the movement of the mobile station.

109. (Currently Amended) An apparatus in a cellular communications network, comprising:

monitoring means for monitoring at least one parameter related to a connection between a mobile station and an support node, said at least one parameter comprising a location of the mobile station; and

determining means for determining ~~if-whether~~ the connection between said support node and said mobile station is to be released ~~dependent-based~~ solely on said at least one parameter monitored by said monitoring means, ~~wherein said at least one parameter comprises a location of the mobile station, and said determining means is configured to determine if the connection should be released based on the location of said mobile station monitored by said monitoring means,~~

wherein the apparatus is configured to provide the connection between the mobile station and the support node, and further configured to completely release the connection based on the location of the mobile station.

110. (Currently Amended) A computer readable storage medium encoded with instructions that, if executed by a computer, perform a process, the process comprising:

establishing a connection between a mobile station and an support node in a communication network through a radio network controller;

monitoring, at the radio network controller, at least one parameter related to the connection between the mobile station and the support node;~~and~~

determining, at the radio network controller, ~~if~~whether the connection between said support node and said mobile station is to be released ~~dependent~~based solely on said at least one parameter; and

releasing completely, by the radio network controller, the connection between said support node and said mobile station based on said at least one parameter.

111. (Currently Amended) The computer readable storage medium as claimed in claim 110, wherein said at least one parameter comprises user activity, and determining ~~releasing to release~~ said connection ~~if~~when there is user inactivity for a predetermined period of time.

112. (Cancelled)

113. (Currently Amended) The computer readable storage medium as claimed in claim 110, wherein the monitoring comprises monitoring only one parameter related to the connection between the mobile station and the support node, is monitored wherein the determining comprises and determining to release releasing the connection between a network element and said mobile station dependent based solely on the only one monitored parameter, monitored.

114. (New) The apparatus of claim 1, wherein the apparatus is a radio network controller.

115. (New) The apparatus of claim 9, wherein the apparatus is a radio network controller.

116. (New) The apparatus of claim 12, wherein the apparatus is a radio network controller.